

# SDE84

## 90 kg Self-contained Ice Cuber

# SIMAG

Other models in this range: SDE18 - SDE24 - SDE30 - SDE 34 - SDE40 - SDE50 - SDE64 - SDE100 - SDE170 - SDE220

### Technical Features

- Stainless steel bodywork - scotch brite
- Air or water cooled
- Vertical pump
- Main switch (ON/OFF)
- Built-in cleaning system
- Easily accessible components
- Low power and water consumption
- Optimum ratio between ice production and bin capacity
- Reduced dimensions
- Double defrosting system
- Refrigerant R134a

### 24 Hour Ice Production - 10°/10° C

Air Cooled      82 kg      No. of cubes 3900

Water Cooled   90 kg      No. of cubes 4280

### Bin Capacity

kg 30

### Warranty

**3** years warranty on components

### Voltage



230/50/1 standard version

220-240/60/1 on demand

### Technology and Certifications



Certified ISO 9001



MILANO OFFICE  
Sales Dept.  
Tel. +39 02 93900215  
e-mail: sales@simag.it  
Service Dept.  
Tel. +39 02 93960357  
e-mail: service@simag.it

SIMAG FAR EAST  
Singapore Office  
Tel. ++65 6738 5393  
e-mail: scotsman@scotsman.com.sg


[www.simag.it](http://www.simag.it)

# SDE84



## 90 kg Self-contained Ice Cuber

Other models in this range: SDE18 - SDE24 - SDE30 - SDE 34 - SDE40 - SDE50 - SDE64 - SDE100 - SDE170 - SDE220



CONTROL BOARD



SPRAY BAR  
New spray bar with nozzles in fixed position



MAIN SWITCH  
New embedded main switch



CLEANING SYSTEM  
Easy cleaning of water pump filter (except SDN20-25)



VENTILATING GRILLE  
New ventilating grille in water cooled version



TOP ANGLE  
New top plastic round corners



AIR FILTER  
New condenser air filter for air cooled version (except SDN20)

### Operating Limits

	Minimum	Maximum
Air Temperatures	10°C	43°C
Water Temperatures	5°C	38°C
Electrical Voltage	-10%	+10%
Water Pressure	14 psi 1 bar	70 psi 5 bar

Specifications and design are subject to change without notice

	Voltage	Power Input Watt (*)	Refrigerant	Refrigerant charge kg	Fuse Amp	Water Consumption l/h (**)	Net Weight kg	Shipping Weight kg
SDE 84 AS	230/50/1	620	R134a	0,60	10	6,9	63	74
SDE 84 AS	220-240/60/1	620	R134a	0,45	10	6,9	63	74
SDE 84 WS	230/50/1	500	R134a	0,40	10	52	63	74
SDE 84 WS	220-240/60/1	500	R134a	0,30	10	52	63	74